



Cordless Hammer Driver Drill
Cordless Driver Drill
Cordless Impact Driver

Satisfy Professional's Needs



Cordless Hammer Driver Drill
DHP482

Cordless Driver Drill
DDF482

Cordless Impact Driver
DTD152

Bits not included.

High Speed



DHP482
1,900 High Speed
 Predecessor model: 1,500rpm



DDF482
1,900 High Speed
 Predecessor model: 1,500rpm



DTD152
2,900 High Speed
 Predecessor model: 2,300rpm

Compact overall length for increased maneuverability

← 198mm DHP482 →



LED Job light with pre-glow functions

On pulling switch trigger, the light automatically turns on before motor starts turning.



Compact belt clip



For use in outdoor applications or harsh environments, protection from dust and dripping water is enhanced.



Battery

- BL1850 : 5.0Ah
- BL1840 : 4.0Ah
- BL1830 : 3.0Ah
- BL1815N : 1.5Ah



Fast Charger DC18RC

* Charging time 22min.

Charger DC18SD

* Charging time 60min.



Dual Rapid Charger DC18RD

* Charging time 45min.



4-Port Charger DC18SF

* Sequential charging time 60min.



* With BL1830 : 3.0Ah

More Torque

DTD152: 165N•m

Predecessor model: 160N•m

DHP482/DDF482: 62N•m

Predecessor model: 50N•m

Ergonomically designed handle with soft grip



A In order to provide maximum thrust to the bit, the top back of the handle is ergonomically contoured and widened according to the U-shape formed between user's thumb and index finger.

B Rubberized soft grip provides comfortable grip and more control while minimizing hand fatigue and pain.

All metal gear construction

All metal gear construction for extra-high transmission durability (DHP482, DDF482)



21 stages Torque Settings

(DHP482, DDF482)
Predecessor model: 16 stages



Cordless Hammer Driver Drill	DHP482 13mm	440
Cordless Driver Drill	DDF482 13mm	440

	DHP482	DDF482
Capacity	Steel : 13mm Wood : 38mm Masonry : 13mm	Steel : 13mm Wood : 38mm
Impacts per minute (ipm)	Hi : 0-28,500 Lo : 0-9,000	-
No load speed (rpm)	Hi : 0-1,900 Lo : 0-600	Hi : 0 - 1,900 Lo : 0 - 600
Max. fastening torque	62N.m	62N.m
Dimensions (L x W x H)	198x79x249mm	185x79x249mm
Net Weight*	1.5kg with BL1815N 1.8kg with BL1850	1.5kg with BL1815N 1.7kg with BL1850

Standard Equipment : Fast Charger, Battery Cartridge, (+) (-) Bit, Belt clip

Cordless Impact Driver	DTD152Z (Available as Skin only)	448
------------------------	----------------------------------	-----

	DTD152Z
Capacity	Machine screw : M4 - M8 (5/32 - 5/16") Standard bolt : M5 - M16 (3/16 - 5/8") High tensile bolt : M5 - M12 (3/16 - 1/2") Coarse thread (in length) : 22 - 125mm (7/8 - 4-7/8")
Impacts per minute (ipm)	0 - 3,500
No load speed (rpm)	0 - 2,900
Max. fastening torque	165N.m
Dimensions (L x W x H)	137x79x238mm
Net Weight*	1.3kg with BL1815N 1.5kg with BL1850

*weight according to EPTA-Procedure 01/2003 Items of standard equipment and specifications may vary by country or area.



Makita New Zealand Ltd.
15 Orbit Drive, Mairangi Bay
PO Box 100 914, North Shore, Auckland 0745
Fax 0800 600 601 Sales 09 479825

Visit our website for information and tool features :
www.makita.co.nz